



Metric table

1

| Dimensions in: millimeters / inches | | | | | | | | | |
|-------------------------------------|---------------|--------------|------------|------------|-------------|------------|------------|------------|-----------|
| l_1 | $l_2 \pm 0.5$ | l_3 | b_1 | b_2 | d | h_1 | h_2 | h_3 | t |
| 115 4.53 | 95.5 3.76 | 75.5 2.97 | 38 1.50 | 19 0.75 | 6.5 0.26 | 35 1.38 | 15 0.59 | 11 0.43 | 5 0.20 |

Specification

- 3
- Handle**

Plastic, Polyamide (PA)

 - Glass fiber reinforced
 - Operating temperature -22 °F to +212 °F (-30 °C to +100 °C)
 - Black-gray, similar to RAL 7021, matte finish
- Cover**

Plastic, Polyamide (PA)

 - Black-gray, RAL 7021, shiny finish
 - Orange, RAL 2004, shiny finish
 - Gray, RAL 7035, shiny finish
 - Yellow, RAL 1021, shiny finish
 - Blue, RAL 5024, shiny finish
 - Red, RAL 3000, shiny finish
- DSG

● DOR

● DGR

● DGB

● DBL

● DRT

When using guards on machines and automation systems, which include double hinged doors, use of a colored cover makes identification of the guard safety handles EN 630.2 easier. Resistant to solvents, oils, grease and other chemical agents. The cover is included but supplied unassembled.

| see also... | Page |
|--|------|
| EN 630 Off-Set Enclosed Safety U-Handles | QVX |
| GN 730 Ledge Handles | QVX |

| Technical Information | |
|---------------------------|-----|
| Strength Values | QVX |
| Plastic Characteristics | QVX |
| Product Family Ergostyle® | QVX |

- RoHS
- On request

 - Various metric and inch size fasteners and kit packaging