



Metric

2 Type

- A** Straight connection
- B** 45° connection
- C** 90° connection

Metric table

1 Size	d ₁ Connection thread for GN 880	3 Length I Hose length			d ₂ Hose connector	d ₃ Nominal hose width	d ₄ ≈
		250	500	1000			
22	M 22 x 1.5	250	500	1000	15	14	15.5
		9.84	19.69	39.37			
26	M 26 x 1.5	250	500	1000	20	19	20
		9.84	19.69	39.37			

Dimensions in: millimeters / inches

Specification

- Connecting nut** with hose connector
Brass
- Connector elbow** 45° / 90°
Copper
- O-ring**
Acrylonitrile butadiene rubber (NBR)
- Drain hose**
Polyvinyl chloride (PVC), transparent **T**
- Hose clip** for Type B / C
Steel, zinc plated
- Plug**
Plastic, Polyethylene (PE-LD)
- RoHS
- On request**
 - Other hose lengths
 - Drain hose with fabric inlay (Nylon)

Connector pieces GN 880.1 are used in connection with fluid drain valves GN 880.

Screwing on the connector piece actuates the valve plate of the fluid drain valve, allowing the fluid to flow through the hose into a pan. The plug prevents the leakage of residual fluid after emptying. The plugs and the hose clip (only type B and C) are included as part of the order.

see also... **GN 880 Fluid Drain Valves** **Page QVX**

Technical Information

Plastic Characteristics **QVX**

How to order (Without drain hose)	1 Size
	2 Type

GN 880.1-26-C

How to order (With drain hose)	1 Size
	2 Type
	3 Hose length I
	4 Hose version

GN 880.1-22-A-500-T