

JMST2.MH61963 - GASKET MATERIALS - COMPONENT

Gasket Materials - Component

See General Information for Gasket Materials - Component

OTTO GANTER GMBH & CO KG

Triberger Strasse 3
78120 Furtwangen, GERMANY

MH61963

Compound No.	End-Use Application(s)
Synthetic rubber EPDM gasket material	
GN2180-EPDM-11.5-D-xx Xx - size of packaging unit [m], Example: -20 = 20m	Investigated to UL 50 and UL 50E, Continuous and Periodic Recompression, enclosure types: 2, 3, 3R, 3S, 3X, 3RX, 3SX, 4, 4X, 5, 6, and 6P.
GN2180-EPDM-13-D-xx	Investigated to UL 50 and UL 50E, Continuous and Periodic Recompression, enclosure types: 2, 3, 3R, 3S, 3X, 3RX, 3SX, 4, 4X, 5, 6, and 6P.
GN2180-EPDM-15.5-A-xx Xx - size of packaging unit [m], Example: -20 = 20m	Investigated to UL 50 and UL 50E, Continuous and Periodic Recompression, enclosure types: 2, 3, 3R, 3S, 3X, 3RX, 3SX, 4, 4X, 5, 6, and 6P.
GN2180-EPDM-20.5-A-xx	Investigated to UL 50 and UL 50E, Continuous and Periodic Recompression, enclosure types: 2, 3, 3R, 3S, 3X, 3RX, 3SX, 4, 4X, 5, 6, and 6P.

The final acceptance of a gasket material in a specific end-use application is dependent on its installation and use, and may require additional evaluation with respect to ingress or leakage of solids (such as dusts), liquids or gases, or other features dependent on the design and construction of the equipment in which it is used.

Marking: Company name and model designation.

Last Updated on 2018-11-20

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2019 UL LLC"